

[Info] How to include domain-specific Apache configuration directives into web server configuration file

- Parallels Plesk Panel 8.x for Linux/Unix
- Parallels Plesk Panel for Linux/Unix
- Parallels Plesk Panel
- Parallels Plesk Panel 9.x for Linux/Unix
- Panels

Resolution

You can include domain-specific Apache configuration directives into the web server configuration file. In Parallels Plesk Panel, each domain has virtual host configuration information stored in a separate file called `httpd.include`.

On all Linux systems, this file is located in the directory `/var/www/vhosts/<domain-name>/conf/`.

On FreeBSD systems, this file is located in the directory `/usr/local/www/vhosts/<domain-name>/conf/`.

If you upgraded from Plesk version 7.5.4 or an earlier version, try looking for one of these files in the directory: `/home/httpd/vhosts/<domain-name>/conf/` or `/usr/local/psa/home/vhosts/<domain-name>/conf/`.

Note: you can change the location of virtual host directories using the **transvhosts.pl** utility, which is located in either the `/usr/local/psa/bin/` or the `/opt/psa/bin/` directory, depending on your operating system.

This file is overwritten each time the virtual host configuration is changed, and thus any manual alterations made to the file are discarded. To use custom directives or redefine those inserted by Plesk, you need to create the files **vhost.conf** and/or **vhost_ssl.conf** with necessary directives in the directory `/path_to_vhosts/<domain-name>/conf/` for a domain, and `/path_to_vhosts/<domain-name>/subdomains/<subdomain-name>/conf/` for a subdomain.

If any of these files exist by the time the main configuration file is generated, Plesk inserts the appropriate "Include" directive into the HTTP and/or HTTPS virtual host context respectively. For security reasons, only the root can create the **vhost.conf** and **vhost_ssl.conf** files.

For the changes to take effect, you need to run the following command:

```
PRODUCT_ROOT_D/admin/sbin/websrvnmng --reconfigure-vhost  
--vhost-name=<domain_name>
```

Additional Information

Below you can find some examples regarding the use of the virtual host configuration file:

[I am getting "open_basedir" error in PHP script](#)

[How to enable 'register_globals' for domain in Plesk?](#)

[How to enable directory indexing for domain?](#)

[How to create wildcard subdomain?](#)

How do I setup JSP pages to run from domain's DocumentRoot directory?

How do I setup all subdomains *.domain.tld to point to a domain domain.tld?

©Parallels, 2013, autogenerated from <http://kb.parallels.com/en/5464>